



Shandong Zhuoxing Chemical Co., Ltd.
Zibo Zhuoxing Enterprises Co., Ltd.

Cement admixture

cement mixture is a generation of Eco-friendly high performance polycarboxylate ether superplasticizer powder developed by our company with DD-909 (TPEG 2400) as main raw material.

Advantages/Characteristics:

- (1) cement mixture with solid content 97% min. is especially optimized for plastification and water reduction of cementitious construction materials.
- (2) Having a good thermostability to 100°C (one hundred degree celsius centigrade).
- (3) High water reducing ratio: make the mortar with water reducing ratio of more than 25%, greatly improve the fluidity of the mortar under the condition of same water content in mortar.
- (4) Provides an excellent development of early strength and high strength.

Mobile/Wechat:0086 13053363281,0086 17865273019

Mail:sales@zhuoxingchem.com,sales02@zhuoxingchem.com

Web site:<https://www.sdzhuoxingpce.com>,www.zhuoxingchem.com



Shandong Zhuoxing Chemical Co., Ltd.
Zibo Zhuoxing Enterprises Co., Ltd.

(5) With a good dispersion, an excellent adaptability to different cements, and good water-reducing properties.

Usages and Cautions:

(1) A recommended dosage is 0.1%–0.6% by the weight of cementitious materials. Actual dosages should be determined by test.

(2) New mixture product is forbidden to be mixed with naphthalene sulphonate.

(3) Compatibility test must be done when it is used together with other admixtures.

(4) Storage should avoid overlying or overweight. After open the package, it should be sealed to prevent damp agglomeration.

Package: Packed in 25kg plastic woven bags with PE inner liner, 16 mt with pallets loaded in one 20' GP, 27 mt with pallets loaded in 40' HQ by sea, 25.5 mt with pallets loaded in 40' HQ by train

Shelf time: 12 months.

Mobile/Wechat: 0086 13053363281, 0086 17865273019

Mail: sales@zhuoxingchem.com, sales02@zhuoxingchem.com

Web site: <https://www.sdzhuoxingpce.com>, www.zhuoxingchem.com



Shandong Zhuoxing Chemical Co., Ltd.
Zibo Zhuoxing Enterprises Co., Ltd.

Application:

1. cement mixture is used for gypsum based and cement based dry mix mortar.

It can also be used for oil well cementing operation.

2. It is especially for cementitious self-leveling underlayments (SLU), plasters and masonry, non-shrink grouts, self-leveling floor screeds, repair mortars, injection mortars, dry mix concrete, tiles adhesives and joint fillers.

Quality Specification

Item	Unit	Standard
Appearance	/	White powder
Density (23℃)	Kg/m ³	500±50
PH (23℃)	/	6.0±1.0
Solid Content	%	97.0±1.0
Moisture content	%	≤3.0
Water Reducing Ratio	%	≥25

Mobile/Wechat:0086 13053363281,0086 17865273019

Mail:sales@zhuoxingchem.com,sales02@zhuoxingchem.com

Web site:<https://www.sdzhuoxingpce.com>,www.zhuoxingchem.com



Shandong Zhuoxing Chemical Co., Ltd.
Zibo Zhuoxing Enterprises Co., Ltd.

Cl ⁻	%	≤0.02
Alkali content	%	≤0.3

Mobile/Wechat:0086 13053363281,0086 17865273019

Mail:sales@zhuoxingchem.com,sales02@zhuoxingchem.com

Web site:<https://www.sdzhuoxingpce.com>,www.zhuoxingchem.com